Analog Panphone Series 4

Antivandal Analog Intercom



Antivandal Intercom for standard analog extension, of high strength and durability with piezoelectric buttons. For indoor or outdoor use.

These intercoms allow automatic dialing to extension on standard PBX by pressing the mechanical pushbutton or dialing on Keyboard.

Versions of Analog Panphone are available for different needs: with numeric keypad or one button or versions with or without IP Color Camera.

They can be used as Intercom or access control with code access by dialing directly on keyboard for the case of versions with Keypad.

Available Versions:

- Surface or Flush mount.
- Numeric Keypad or One Button
- With IP Color Camera

They have 2 dry contact relays that operate independently, for connection of electric gates, which can be activated from remote extension or on the same keyboard.

They can also be activated from external devices such as card readers, biometric readers, etc.. In addition they have digital inputs that can be connected to switches and sensors.

Thanks to the IP55 casing and installation versatility, it facilitates the use in outdoors and in hygienic environments that requires constant cleaning.

They operate in standard PBX via analog extensions.

They works with all telephone PBXs that have conventional analog extensions, which allows clients to use the existing telephony infrastructure to add intercom capabilities.









Surface 187x104x32mm

Flush Mount 217,41x128,8x8,6mm

Applications:

- Centralized Access Control for different corporate locations or access doors.
- Unattended gatehouses or guardhouses.
- Healthcare and geriatric environments.
- Parking barriers and Tollgates.
- Flevators.
- Roadside Emergency Callers (SOS points).
- Public Transport Stations.
- Systems of accessibility for people with disabilities.
- Intercom in prisons.
- Vending Machines.
- Intercom for operating rooms and hospitals, etc.
- PA Systems.

Ciser System S. L. U. C/ Casas de Miravete 24, Portal B Planta 1 Puerta 1

28031 Madrid - España/Spain +34 911927757





comercial@cisersystem.com www.cisersystem.com



General Features of Analog Panphone Series 4

Handsfree Intercom with automatic hang up and hook off	Yes	Independent dry contact relays, ideal for connect		
Antivandal	Yes	or external devices. Controllable for normally open		
Resistance Grade	IP 55			
Voice Connection	Analog Extension or PSTN	Inputs for external push buttons or sensors.		
Automatic call to extension from Call button	Yes	Cabling		
Call duration time limit	Yes	Power source		
Manually adjustable Volume in microphone and speaker (Gain Control)	Yes	Individual Power adaptor 12V DC 1.8 Amp.		
Opens doors remotely (relay activation) by code dialing from any extension or external phone.	Yes	Configuration by DTMF		

Independent dry contact relays, ideal for connecting electrical-activation doors or external devices. Controllable for normally open or closed.	2
Inputs for external push buttons or sensors.	1
Cabling	2 wires + Power source DC
Power source	12V DC
Individual Power adaptor 12V DC 1.8 Amp.	Included
Configuration by DTMF	Yes

Features of Analog Panphone Series 4 according to version

	Analog Panphone Series 4 (without Camera)				Analog Panphone Series 4 (with Camera)			
Reference	4006	4003	4018	4015	4008	4005	4020	4017
Format	Surface		Flush mount		Surface		Flush mount	
Piezoelectric Button or numeric Keypad	1 Button	Keypad	1 Button	Keypad	1 Button	Keypad	1 Button	Keypad
Door opening by code dialing	No	Yes	No	Yes	No	Yes	No	Yes
Dial to specific extension	No	Yes	No	Yes	No	Yes	No	Yes
10 number memory for Speed Dial	No	Yes	No	Yes	No	Yes	No	Yes
Dimensions (HxWxD) mm	187x104x32 217,41x128,8x8,6			187x104x32 217,41x128,8x8,6				
Color Camera	No				Yes, IP or Analog			
Supports IP Video	No				Yes, only IP Camera			
IP Video server Included	No				Yes, only IP Camera			
Additional Cabling for camera	N/A				UTP (Ethernet) IP camera/Coaxial Analog Camera			
Card Reader	Optional			Optional				
Speaker Power	Up to 1W			Up to 1W				
Echo Cancellation	Yes				Yes			