


CXR2000 CompletePBX Telephony System for SMB

The CXR2000 is an Intel Atom® based stand-alone telephony solution with PSTN / telephone ports. The CXR2000 features Xorcom's CompletePBX distribution with up to 32 analog ports, up to eight BRI ISDN ports, and/or a single PRI/R2/CAS ISDN E1/T1 port. The CXR2000 supports up to 160 PSTN / Analog phones ports with external Astribank units, up to 200 users and up to 85 concurrent calls.



[To see the different CXR2000 configurations on our Web site click here.](#)

Features

- Unlimited extensions, voicemail boxes, hunt groups, call center groups, and auto attendants (IVRs)
- Basic built-in call center with call recording, barge and whisper
- Emergency notification module
- Endpoint manager
- User-friendly Web interface
- Interface in different languages
- CDR (Call Details Record)
- TDM/SIP/IAX trunks
- Remote extensions
- Voicemail
- Voicemail to email
- Web access to voicemail
- Fax support
- Fax to email
- IVR menu system
- Ring groups
- Call queues
- Conference rooms
- Find me / Follow me
- VmX Locator
- Time-based routing
- Advanced dialing rules
- Music-on-hold
- Paging and intercom
- Admin status screen
- Package manager (for easy updates)
- Network settings tool

Software

Software version	Xorcom's CompletePBX version 4.x
Linux version	CentOS 6.5
GUI	Based on FreePBX (base version: 2.11)
Security	Intrusion protection software; firewall protection
Rapid Tunneling™	Utility providing secure remote access for product support purposes


Hardware

Processor	Intel Atom D2500 Dual Core 1.8 GHz
RAM	2 GB
Hard disk	From 320GB 2.5" (500GB optional)
Echo Cancellation Module	Voice enhancement & echo cancellation (optional)
Analog Lines Fail-over Kit	In case of power outage or an Asterisk malfunction, up to six analog PSTN lines are routed directly to predetermined analog extensions (optional and model-specific)
USB	4 external USB 2.0
I/O Ports	Input/Output ports for Asterisk peripheral device support (model-specific)
Rapid PA™	Public Address capability for FXS port(s) (optional and model-specific)

Telephony

Maximum number of concurrent calls	85 (SIP only); 45 (PRI + FXS)
Maximum number of built-in analog ports	32 (additional ports with external Astribank units)
Number of E1 / T1 ports	1 (up to 30 concurrent PRI/R2/CAS calls)
Maximum telephony modules supported internally	4 (additional Astribank ports are supported by adding Astribank units)
Maximum number of telephony ports supported internally	54 (E1 PRI/R2/CAS + 24 analog ports)
Supported Xorcom telephony modules	<ul style="list-style-type: none"> • 8 FXS ports • 8 FXS ports + I/O ports • 8 FXO ports • 2 FXO ports, 6 FXS ports + I/O ports • 6 FXO ports, 2 FXS ports • 1 PRI/R2/CAS port • Up to 8 BRI ISDN ports

Power

Power supply	Internal
Voltage	Switching, auto adjust 100/240 Volts, 50/60 Hz
Power consumption	230 Watts (maximum)
Built in grounding connection	

Network

Ethernet port	10/100/1000 Mb/s
---------------	------------------

Maintenance and Support

- Monitor and keyboard support
- [Rapid Recovery™](#) backup utility provided on Disk-on-Key
- [Rapid Tunneling™](#) utility providing secure remote access for product support purposes
- Internet updates

Environment

Storage temperature	-20° to 70° Celsius (-4° -158° F)
Working temperature	0° to 40° Celsius (32° -104° F)
Humidity	20%-95%, non-condensing

Dimensions and Weight

Weight	8 Kg 18Lbs (weight depends on configuration)
Size	19" 2U industry standard rack-mountable chassis

Specifications may change without prior notice.