

GSM Panphone Series C

Antivandal GSM Intercom



Anti-vandalism intercom for cellphone line, high strength and durability with mechanical pushbutton and surface installation, for outdoor or indoor use.

These Panphone maintain the functionality of the traditional but varying its external presentation format. The **GSM Panphone Series C** are equipments for installation on the surface with a treated aluminum case, painted, hermetic closure with security screws and mechanical push-buttons.

Their physical characteristics and components also offer high resistance and durability, allowing the use in outdoors in difficult weather conditions. They are baked painted with colors for specific communication applications like Gray (Normal), Yellow (Information) and Red (SOS).

Ideal for places where wiring (for voice or data) is not possible or is not required.

Available Versions:

- ✓ Surface installation
- ✓ One Button
- ✓ Colors Gray, Red and Yellow
- ✓ Pre-recorded messages in Spanish (ESP), English (ENG), Portuguese (PT), Catalan (CAT) and other languages can be added.

These intercoms can make automatic dialing to a phone number through the Mobile Cellular Network by pressing the Call button. The dialing is sequential of up to 9 pre-configured destination numbers in case of call error or no answer.

The **GSM Panphones** play pre-recorded audios to indicate call or activity status (call in progress, open door, etc.) configurable in several languages.

They have 2 independent dry contact relays, for connection of electric doors, which can be activated from a remote telephone (with code, SMS or missed call) from list of allowed numbers (up to 256). Additionally, they can be activated from external devices (such as card readers, biometrics, proximity readers, etc.), since they have digital inputs for connecting pushbuttons and sensors.

Send SMS to a defined telephone destination, with the activation of an alarm or sensor (eg door opening, presence detector, etc.).

The configuration is simple and friendly through instructions that are sent by SMS messages.

They operate in common frequency bands of Mobile Cellular Networks

They operate in 850, 900, 1800 and 1900 MHz frequency bands allowing its use in coverage areas of the different Mobile Voice Networks.



Yellow (RAL 1023)

Red (RAL 3020)

Surface (188x115,9x40mm)

Applications:

- Centralized Access Control for different corporate locations or access doors.
- Unattended gatehouses or guardhouses.
- Remote sites and difficult to access.
- Parking barriers and Tollgates.
- Garages.
- Elevators.
- Roadside Emergency Callers (SOS points).
- Public Transport Stations.
- Non attended Fuel stations, self-service.
- Systems of accessibility for people with disabilities.
- Intercom in prisons.
- Vending Machines.

Ciser System S. L. U.

C/ Casas de Miravete 24,
Portal B Planta 1 Puerta 1
28031 Madrid - España/Spain
+34 911927757

comercial@cisersystem.com
www.cisersystem.com



General Features of GSM Panphone Series C

Handsfree Intercom with automatic hang up and hook off	Yes	Configuration of allowed numbers and white list for incoming calls and activation of Relays (up to 256).	Yes
High strength aluminum mounting box	Yes	Automatic adjustable Volume for microphone and speaker (Gain Control)	Yes
Treated, baked paint, High durability and resistance to weathering and climatic incidents	Yes	Opens doors remotely (relay activation) via dialing code from any external phone, missed call or SMS.	Yes
Grip with safety screws	Yes	Permits to program allowed numbers to activate relays	Yes
Antivandal	Yes	Independent dry contact relays, ideal for connecting electrical-activation doors or external devices. Controllable for normally open or closed.	2
Voice Connection	Mobile Network	Inputs for external push buttons or sensors.	1
Wireless Coverage	Mobile Network Coverage	SMS Notification by relay activation	Yes
SIM Card support	1 SIM (Format normal)	Cabling	Power source DC
Frequency Bands	850 - 900 - 1800 - 1900 Mhz	Power source	12V DC
Automatic call dialing to Phone number from Call button	Yes	Individual Power adaptor 12V DC 1.8 Amp.	Included
Sequential dialing up to 9 numbers on error or no answer call.	Yes	Configuration via SMS	Yes
Call duration time limit	Yes	Audio Quality improvement with external noise isolation.	Yes
Pre-recorded Audio Messages in multiple languages for state and activity indication. Available Spanish, English, Portuguese, Catalan and other languages can be added.	Yes	Alarm or open/closed door detection	Yes

Features of GSM Panphone Series C according to version

Reference	GSM Panphone		
	C040	C040-A	C040-R
Treated (baked) High Durability Paint	Textured Gray RAL 9006	Yellow RAL 1023	Red RAL 3020
Format	Surface		
Button or numeric Keypad	1 mechanical pushbutton		
Door opening by code dialing or specific extension	No		
Memory numbers for Speed Dial, up to 256	No		
Dimensions (HxWxD) mm	188x115,9x40		
Color Camera	No		
Card Reader	No		
Speaker Power	Up to 1W		
Echo Cancellation	Yes		